



Rock Cutter Bits

Body Parts - Series DB-400

Part Number	Part Name	Approximate Wt.	
		Lbs.	Kg.
H043	Bit Shank, 3-Blade	1.9	0.86
H142	Locking Bowl	1.4	0.63
H341	3-Blade Reaming Stabilizer (slip-on, friction-held, no threads). Reamers should conform to bit blade size. (Not to be used when using connectors with breakout lugs)	2.7	1.22
H241-0012	2 ³ / ₈ " Mayhew Regular Tool Joint Box Connector with breakout lugs	6.6	2.99
H241-0014	2 ³ / ₈ " Failing Exploration Tool Joint Box Connector with breakout lugs	6.7	3.04
H241-1614	2 ³ / ₈ " Failing CFD-1 16" (406.4mm) Length Tool Joint Box Connector with breakout lugs	14	6.35
H241-1314	2 ³ / ₈ " Failing CFD-2 13" (330.2mm) Length Tool Joint Box Connector with breakout lugs	13	5.9
H242-0001	2 ³ / ₈ " A.P.I. Regular Tool Joint Pin Connector with breakout lugs	11	4.99
H241-0011	Mayhew Junior Tool Joint Box Connector with breakout lugs	6.6	2.99
H243-0069	Carey Midget Tool Joint Box Connector*	2.9	1.31
H243-0045	3-Thread N-Rod Box Connector*	3	1.36
H243-0039	4-Thread N-Rod Box Connector*	3	1.36

Blade Size		Approximate Wt. - Box of 12 Sets			
Inches	mm	Rock Cutter 3-Blade		Carbide Insert 3-Blade	
		Lbs.	Kg.	Lbs.	Kg.
NX (2 ¹ / ₂)*	75.4	36	16.3	36	16.3
3*	76.2	36	16.3	36	16.3
3 ¹ / ₂ *	82.5	38	17.2	38	17.2
3 ³ / ₄	85.7	38	17.2	38	17.2
3 ¹ / ₂ *	88.9	40	18.1	40	18.1
3 ³ / ₄	92.1	40	18.1	40	18.1
3 ³ / ₄ *	95.2	40	18.1	40	18.1
3 ⁷ / ₈	98.4	40	18.1	40	18.1
4*	101.6	42	19	42	19
4 ¹ / ₈	104.8	42	19	42	19
4 ¹ / ₄ *	108	42	19	42	19